



Engine

Engine	4-stroke, single-cylinder, OHV, air-cooled
Transmission	Continuously Variable Transmission (CVT) with (H,N,R)
Displacement	401cc
Bore x Stroke	82.0 x 76.0mm
Compression Ratio	8.6:1
Fuel System	Nikki 6C1026 carburetor
Ignition	Magneto and transistor
Engine Braking	No

Suspension

Front Suspension / Wheel Travel	MacPherson Strut/3.1 in
Rear Suspension / Wheel Travel	Unit Swingarm/3.1 in
Front Tires	22x9-10 bias
Rear Tires	22x11-10 bias
Steering	Rack-and-pinion
Ground Clearance	6.1 in
Wheelbase	70.1 in

Brakes

Front Brakes	Hydraulic drums, sealed
Rear Brakes	Hydraulic drums, sealed

Totals

Overall Length	106.7 in
Maximum Torque	21.7 lb-ft @ 2400 rpm
Overall Width	52.6 in
Overall Height	70.1 in
Curb Weight	967.6 lb**
Fuel Capacity	4.2 gal
Turning Radius	10.8 ft
Cargo Bed Capacity	400 lb
Load Capacity	926 lb
Seating Capacity	2
Towing Capacity	1100 lb

General

Frame Type	Steel tube ladder type
Final Drive	2WD, shaft. Dual mode rear differential with differential lock
Cargo Bed Dimensions (LxWxH)	35.6 x 40.9 x 9.6 in
Lighting	(2) Halogen headlights, tail/brake lights
Instruments	Fuel gauge, hour meter, oil temp light, parking brake light
Alternator Output (max)	17 amp
Color Choices	Timberline Green, Dark Royal Red

Guarantee

Warranty	Kawasaki 3-Year Limited Warranty
----------	----------------------------------