



Engine

Engine	4-stroke, 3-cylinder, DOHC, liquid-cooled, gas
Transmission	Continuously Variable Transmission (CVT) with (H,L,N,R)
Displacement	812cc
Fuel System	DFI® with 34mm throttle body
Engine Braking	Yes
Suspension	
Front Suspension / Wheel Travel	Double wishbone/8.7 in
Rear Suspension / Wheel Travel	Double wishbone/8.5/8.7 in
Steering	Electric Power Steering (EPS) / rack-and-pinion, (Non EPS rack-and-pinion)
Ground Clearance	10.4 in
Wheelbase	92.3 in

Totals

Overall Length	133.3 in
Maximum Torque	48.0 lb-ft @ 3500 rpm
Overall Width	64.0 in
Overall Height	79.7 in (EPS LE) / 77.4 (EPS, Non EPS)
Curb Weight	1832.4 lb (EPS LE) / 1830.2 (EPS) / 1816.9 (Non EPS)**
Fuel Capacity	7.9 gal
Turning Radius	16.0 ft
Cargo Bed Capacity	1000 lb (600 lb for California models)
Load Capacity	1616 lb
Seating Capacity	3
Towing Capacity	2000 lb

General

Final Drive	Selectable 2WD/4WD, shaft. Dual mode rear differential with differential lock
Cargo Bed Dimensions (LxWxH)	54.1 x 53.3 x 11.0 in
Lighting	(2) Halogen (high/low beam) headlights. LE (2 additional auxiliary LED headlights (high/low beam)

Instruments

Instruments	Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT warning indicator, neutral, reverse and parking indicators, seatbelt reminder lamps
-------------	---

Alternator Output (max)

Color Choices

Guarantee

Warranty

75 amp

Timberline Green, Bright White

Kawasaki 3-Year Limited Warranty