



Engine

Engine	4-stroke, 3-cylinder, OHV, liquid-cooled, diesel
Transmission	Continuously Variable Transmission (CVT) with high, low, neutral, reverse gears
Displacement	993cc
Fuel System	Bosch in-line injection pump
Engine Braking	Yes

Suspension

Front Suspension / Wheel Travel	Double wishbone / 8.7 in
Rear Suspension / Wheel Travel	Double wishbone / 8.5 / 8.7 in
Front Tires	26x9-12 Duro Bias ply
Rear Tires	26x11-12 Duro Bias ply
Steering	Electric Power assisted rack-and-pinion (EPS)
Ground Clearance	10.2 in
Wheelbase	92.3 in

Brakes

Front Brakes	Disc
Rear Brakes	Disc

Totals

Overall Length	133.3 in
Maximum Torque	38.3 lb-ft @ 2400 rpm
Overall Width	64.0 in
Overall Height	77.6 in
Curb Weight	1936 lb**
Fuel Capacity	7.9 gal
Turning Radius	16.0 ft
Cargo Bed Capacity	1000 lb (1 row configuration) 350 lb (2 row configuration)
Load Capacity	1581 lb
Seating Capacity	3-6
Towing Capacity	2000 lb

General

Final Drive	Shaft, selectable 4-wheel drive with dual-mode rear differential, 2WD/4WD/4WD with rear differential lock
Cargo Bed Dimensions (LxWxH)	42.7 x 53.7 x 11.0 in (1 row configuration) 22.0 x 53.7 x 11.0 in (2 row configuration)
Lighting	(2) Halogen (high/low beam) headlights
Instruments	Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, CVT warning indicator, neutral, reverse and parking indicators, seatbelt reminder lamps
Alternator Output (max)	55 amp

Guarantee

Warranty	Kawasaki 3-Year Limited Warranty
----------	----------------------------------