



Engine

Park Brake Type	Independent, Mechanical Drum
Engine	4-stroke, single-cylinder, OHV, air-cooled
Transmission	Continuously Variable Transmission (CVT) with (H,L,N,R)
Displacement	401cc
Bore x Stroke	3.23x2.99 in
Compression Ratio	8.6:1
Fuel System	Fuel injection
Engine Braking	No

Suspension

Front Suspension / Wheel Travel	MacPherson Strut/3.1 in
Rear Suspension / Wheel Travel	Unit Swingarm/3.1 in
Front Tire	24x9.00-10
Front Tires	24x9.00-10
Rear Tire	24x11.00-10
Rear Tires	24x11.00-10
Wheel Type	Steel
Steering	Rack-and-pinion, Tilt steering
Ground Clearance	6.7 in
Wheelbase	70.1 in

Brakes

Front Brakes	Drum
Rear Brakes	Drum

Totals

Overall Length	106.7 in
Maximum Torque	21.4 lb-ft @ 2400 rpm
Overall Width	52.6 in
Overall Height	70.9 in
Curb Weight	1031.9 lb**
Fuel Capacity	4.2 gal
Turning Radius	10.8 ft
Cargo Bed Capacity	400 lb
Load Capacity	915 lb
Seating Capacity	2
Towing Capacity	1100 lb*

General

Final Drive	Selectable 2WD/4WD, shaft. Dual mode rear differential with differential lock
Cargo Bed Dimensions (LxWxH)	35.6 x 40.9 x 9.6 in
Lighting	(2) Halogen headlights, (2) Halogen tail/brake lights
Instruments	Fuel gauge, hour meter, oil temp light, parking brake light
Alternator Output (max)	22.9 amp
Color Choices	Timberline Green, Dark Royal Red

Guarantee

Warranty	Kawasaki 3-Year Limited Warranty
----------	----------------------------------