



Engine

Engine	4-stroke, SOHC, 4-valve V-twin, liquid-cooled
Starting System	Electric
Transmission	Automatic CVT with centrifugal clutch (H,L,N,R)
Displacement	783cc
Bore x Stroke	85.0 x 69.0mm
Compression Ratio	10.7:1
Fuel System	DFI® with two 36mm Mikuni throttle bodies
Ignition	TCBI with electronic advance
Engine Braking	Yes

Suspension

Front Suspension / Wheel Travel	Double Wishbone; Fox Podium coil-over shocks with piggyback reservoir, adjustable preload and 24-way compression damping/8.0 in.
Rear Suspension / Wheel Travel	Double Wishbone; Fox Podium coil-over shocks with piggyback reservoir, adjustable preload and 24-way compression damping/8.3 in.
Front Tires	Maxxis 27 x 9-14
Rear Tires	Maxxis 27 x 11-14
Wheel Type	Alloy
Steering	Electric Power Steering (EPS) / rack-and-pinion
Ground Clearance	11.2 in
Wheelbase	85.6 in

Brakes

Front Brakes	Dual hydraulic discs with two-piston calipers
Rear Brakes	Sealed, oil-bathed, multi-disc

Totals

Overall Length	125.4 in
Maximum Torque	47.0 lb-ft@ 5500 rpm
Overall Width	60.0 in
Overall Height	79.7 in
Curb Weight	1628.8 lb**
Fuel Capacity	7.9 gal
Turning Radius	16.7 ft
Cargo Bed Capacity	249 lb
Load Capacity	1109 lb
Seating Capacity	4
Towing Capacity	1300 lb

General

Frame	Steel Tube Double-X Reinforcement
Final Drive	Selectable 2WD/4WD with locking front differential, shaft
Cargo Bed Dimensions (LxWxH)	17.9 x 47.6 x 8.7 in
Lighting	(4) LED headlights, (2) LED taillights, LED stoplight
Instruments	Multi-function digital meter with speedometer, fuel gauge, clock, hour meter, odometer, dual trip meter and parking-brake indicator, R/N/ P/4WD, water temp and low-oil-pressure indicators
Color Choices	Candy Lime Green, Atomic Silver, Fragment Camo Gray

Guarantee

Warranty	Kawasaki 3-Year Limited Warranty
----------	----------------------------------