



Engine

Engine	4-stroke, 2-cylinder, OHV, 90° V liquid-cooled
Transmission	Continuously Variable Transmission (CVT) with high and low range, forward, neutral and reverse
Displacement	617cc
Bore x Stroke	76.0 x 68.0mm
Compression Ratio	10.3:1
Fuel System	DFI® with 34mm Mikuni throttle body

Suspension

Rear Suspension / Wheel Travel	Semi-independent, De Dion axle with leaf springs and shocks/2.8 in
Front Suspension / Wheel Travel	Independent, MacPherson strut/3.9 in
Front Tires	23x11-10 tubeless
Rear Tires	23x11-10 tubeless
Steering	Electric power assisted rack-and-pinion (EPS)
Ground Clearance	7.1 in
Wheelbase	85.2 in

Brakes

Front Brakes	4-wheel hydraulic drums, sealed
Rear Brakes	4-wheel hydraulic drums, sealed

Totals

Overall Length	128.5 in
Maximum Torque	34.7 lb-ft @ 2500 rpm
Overall Width	58.5 in
Overall Height	75.8 in
Curb Weight	1586.9 lb**
Fuel Capacity	6.3 gal
Turning Radius	12.8 ft
Cargo Bed Capacity	800 lb (1 row configuration) 400 lb (2 row configuration)
Load Capacity	1330 lb
Seating Capacity	4
Towing Capacity	1200 lb

General

Final Drive	Shaft, selectable 4-wheel drive with dual-mode rear differential, 2WD/4WD rear differential lock
Cargo Bed Dimensions (LxWxH)	50.4/30.3 x 47.6 x 11.2 in
Lighting	(2) Halogen headlights (2) Tail/brake lights
Instruments	Parking brake warning light, coolant temperature warning light, horn, 12V DC outlet
Alternator Output (max)	23 amp

Guarantee

Warranty	Kawasaki 3-Year Limited Warranty
----------	----------------------------------