



Engine

Engine	4-stroke, 4-cylinder, DOHC, 4-valve, liquid-cooled
Transmission	6-speed
Displacement	1,352cc
Bore x Stroke	84.0 x 61.0mm
Compression Ratio	10.7:1
Fuel System	DFI® with 40mm throttle bodies (4)
Ignition	TCBI with digital advance

Suspension

Rake / Trail	26.0°/4.4 in
Front Suspension / Wheel Travel	43mm inverted, telescopic fork with adjustable rebound damping and spring preload/4.4 in
Rear Suspension / Wheel Travel	Tetra-Lever with stepless rebound damping adjustment and remote spring preload adjuster/5.4 in
Front Tire	120/70 ZR-17
Rear Tire	190/50 ZR-17
Ground Clearance	4.9 in
Wheelbase	59.8 in

Brakes

Front Brakes	Dual floating 310mm petal-style rotors with four-piston calipers, ABS
Rear Brakes	Single 270mm petal-style rotor, single-piston caliper, ABS

Totals

Overall Length	87.8 in
Overall Width	31.1/39.4 wo/w saddlebags
Overall Height	52.9 in/57.7 in (windshield down/up)
Seat Height	32.1 in
Curb Weight	690.2 lb (672.5 w/o saddlebags)
Fuel Capacity	5.8 gal

General

Frame Type	Monocoque Aluminum
Final Drive	Tetra-Lever shaft drive
Color Choices	Metallic Carbon Gray/Metallic Flat Spark Black

Guarantee

Warranty	36 Month Limited Warranty
----------	---------------------------