



Engine

Engine	4-stroke, 4-cylinder, DOHC, 4-valve, liquid-cooled
Transmission	6-speed, return shift
Displacement	998cc
Bore x Stroke	76.0 x 55.0mm
Compression Ratio	13.0:1
Fuel System	DFI® with 47mm Mikuni throttle bodies (4) with oval sub-throttles, two injectors per cylinder
Ignition	TCBI with digital advance and Sport-Kawasaki Traction Control (S-KTRC)

Suspension

Rake/Trail	25.0°/4.2 in
Front Suspension / Wheel Travel	43mm inverted Balance Free Fork, adjustable stepless rebound and compression damping, spring preload adjustability/4.7 in
Rear Suspension / Wheel Travel	Horizontal back-link with Balance Free gas-charged shock, stepless, dual-range (low-/high-speed) compression damping, stepless rebound damping, fully adjustable spring preload/4.5 in
Front Tire	120/70 ZR17
Rear Tire	190/55 ZR17
Ground Clearance	5.7 in
Wheelbase	56.7 in

Brakes

Front Brakes	Kawasaki Intelligent anti-lock Brake System (KIBS), dual semi-floating 330mm discs with dual radial mounted Brembo® monobloc 4-piston calipers
Rear Brakes	KIBS-controlled, single 220mm disc with aluminum single-piston caliper

Totals

Overall Length	82.1 in
Maximum Torque	84.6 lb-ft @ 11,000 rpm
Overall Width	29.1 in
Overall Height	45.1 in
Seat Height	32.9 in
Curb Weight	454.2 lb**
Fuel Capacity	4.5 gal

General

Frame Type	Aluminum perimeter
Final Drive	Sealed chain
Electronic Rider Aids	Kawasaki Launch Control Mode (KLCM), Kawasaki Intelligent anti-lock Brake System (KIBS), Kawasaki Sport Traction Control (S-KTRC), Kawasaki Engine Brake Control, Kawasaki Quick Shifter (KQS) (dual direction), Kawasaki Cornering Management Function (KCMF)
Color Choices	Lime Green

Guarantee

Warranty	12 Month Limited Warranty
----------	---------------------------