



Engine

Engine	2-stroke, 1-cylinder, piston reed valve, water-cooled
Transmission	6-speed, return shift
Displacement	99cc
Bore x Stroke	52.5 x 45.8mm
Compression Ratio	10.2:1 (low speed) - 8.7:1 (high speed)
Fuel System	Keihin PWK28
Ignition	CDI with digital advance

Suspension

Rake / Trail	29°/4.3 in
Front Suspension / Wheel Travel	36mm inverted telescopic cartridge fork with 20-way compression damping/10.8 in
Rear Suspension / Wheel Travel	Uni-Trak® single shock system with 24-way compression and 21-way rebound damping plus adjustable spring preload/10.8 in
Front Tire	70/100-19
Rear Tire	90/100-16
Ground Clearance	13.0 in
Wheelbase	51.6 in

Brakes

Front Brakes	Disc
Rear Brakes	Disc

Totals

Overall Length	75.6 in
Overall Width	30.1 in
Overall Height	45.3 in
Seat height	34.3 in
Curb Weight	169.7 lb**
Fuel Capacity	1.32 gal

General

Frame Type	High-tensile steel perimeter design with subframe member
Final Drive	Chain
Color Choices	Lime Green

Guarantee

Warranty	Not Available
----------	---------------