



Engine

Engine	4-stroke, 2-cylinder, OHV 90° V Liquid-cooled
Transmission	Continuously Variable Transmission (CVT) with forward and reverse
Displacement	617cc
Bore x Stroke	76.0 x 68.0mm
Compression Ratio	10.3:1
Fuel System	DFI® w/ 34mm Mikuni throttle body

Suspension

Rear Suspension / Wheel Travel	Semi-independent, De Dion axle with leaf springs and shocks/2.8 in
Front Suspension / Wheel Travel	Independent, MacPherson strut/3.9 in
Front Tires	23x11-10 tubeless
Rear Tires	23x11-10 tubeless
Steering	Rack-and-pinion
Ground Clearance	7.5 in
Wheelbase	73.6 in

Brakes

Front Brakes	4-wheel hydraulic drums, sealed
Rear Brakes	4-wheel hydraulic drums, sealed

Totals

Overall Length	116.7 in
Maximum Torque	34.7 lb-ft @ 2500 rpm
Overall Width	62.0 in
Overall Height	75.8 in
Curb Weight	1338.4 lb**
Fuel Capacity	6.3 gal
Turning Radius	11.0 ft
Cargo Bed Capacity	800 lb
Load Capacity	1330 lb
Seating Capacity	2
Towing Capacity	1200 lb

General

Final Drive	Shaft, dual-mode rear differential dual-model differential
Cargo Bed Dimensions (LxWxH)	46.3 x 51.6 x 11.4 in
Lighting	(2) Halogen headlights (2) Tail/brake lights
Instruments	Parking brake and coolant temp warning lights, horn, 12V DC outlet
Alternator Output (max)	23 amp

Guarantee

Warranty	Kawasaki 3-Year Limited Warranty
----------	----------------------------------