



Engine

Park Brake Type	Independent, Mechanical Disc
Engine	4-stroke, 3-cylinder, OHV, liquid-cooled, diesel
Transmission	Continuously Variable Transmission (CVT) with (H,L,N,R)
Displacement	993cc
Bore x Stroke	2.91x3.03 in
Compression Ratio	23.5:1
Fuel System	Bosch in-line injection pump
Engine Braking	Yes

Suspension

Front Suspension / Wheel Travel	Double wishbone/8.7 in
Rear Suspension / Wheel Travel	Double wishbone/8.5 (L) /8.7 (R) in
Front Tire	
Front Tires	26x9.00-12
Rear Tire	
Rear Tires	26x11.00-12
Wheel Type	Steel
Steering	Electric Power Steering (EPS), Tilt steering
Ground Clearance	10.4 in
Wheelbase	92.3 in

Brakes

Front Brakes	Dual Disc, 2 piston caliper
Rear Brakes	Dual Disc, 1 piston caliper

Totals

Overall Length	133.3 in
Maximum Torque	38.3 lb-ft @ 2400 rpm
Overall Width	64.0 in
Overall Height	77.4 in
Curb Weight	1852.2 lb**
Fuel Capacity	7.9 gal
Turning Radius	16.0 ft
Cargo Bed Capacity	1000 lb
Load Capacity	1581 lb
Seating Capacity	3
Towing Capacity	2000 lb

General

Final Drive	Selectable 2WD/4WD, shaft. Dual mode rear differential with differential lock
Cargo Bed Dimensions (LxWxH)	54.1 x 53.3 x 11.0 in
Lighting	(2) Halogen headlights, (2) Halogen tail/brake lights
Instruments	Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, glow plug indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators, seatbelt reminder lamps
Alternator Output (max)	55 amp
Color Choices	Bright White, Timberline Green

Guarantee

Warranty	Kawasaki 3-Year Limited Warranty
----------	----------------------------------