



Engine

Engine	4-stroke, 3-cylinder, DOHC, liquid-cooled, gas
Transmission	Continuously Variable Transmission (CVT) with high, low, neutral, reverse gears
Displacement	812cc
Fuel System	Digital Fuel Injection (DFI®)
Engine Braking	Yes

Suspension

Front Suspension / Wheel Travel	Double wishbone / 8.7 in
Rear Suspension / Wheel Travel	Double wishbone / 8.5 / 8.7 in
Front Tires	26x9.00 R12 Radial Duro Frontier
Rear Tires	26x11.00 R12 Radial Duro Frontier
Steering	Electric power assisted rack-and-pinion (EPS)
Ground Clearance	10.4 in
Wheelbase	92.3 in

Brakes

Front Brakes	Disc
Rear Brakes	Disc

Totals

Overall Length	133.3 in
Maximum Torque	48.0 lb-ft @ 3500 rpm
Overall Width	64.0 in
Overall Height	79.7 in
Curb Weight	1832.4 lb**
Fuel Capacity	7.9 gal
Turning Radius	16.0 ft
Cargo Bed Capacity	1000 lb (California model 600 lb)
Load Capacity	1616 lb
Seating Capacity	3
Towing Capacity	2000 lb

General

Final Drive	Shaft, selectable 4-wheel drive with dual-mode rear differential, 2WD/4WD/4WD with rear differential lock
Cargo Bed Dimensions (LxWxH)	54.1 x 53.3 x 11.0 in
Lighting	(2) Halogen (high/low beam) headlights, (2) additional auxiliary LED headlights (high/low beam)
Instruments	Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT warning indicator, neutral, reverse and parking indicators, seatbelt reminder lamps
Alternator Output (max)	75 amp

**

Guarantee

Warranty	Kawasaki 3-Year Limited Warranty
----------	----------------------------------