



Engine

Park Brake Type	Independent, Mechanical Disc
Engine	4-stroke, 3-cylinder, DOHC, liquid-cooled, gas
Transmission	Continuously Variable Transmission (CVT) with (H,L,N,R)
Displacement	812cc
Bore x Stroke	2.83x2.62 in
Compression Ratio	9.5:1
Fuel System	DFI® with 34mm throttle body
Engine Braking	Yes

Suspension

Front Suspension / Wheel Travel	Double wishbone/8.7 in
Rear Suspension / Wheel Travel	Double wishbone/8.5 (L) /8.7 (R) in
Front Tire	
Front Tires	27x9.00-12, radial
Rear Tire	
Rear Tires	27x11.00-12, radial
Wheel Type	Alloy
Steering	Electric Power Steering (EPS), Tilt steering
Ground Clearance	10.8 in
Wheelbase	79.7 in

Brakes

Front Brakes	Dual Disc, 2 piston caliper
Rear Brakes	Dual Disc, 1 piston caliper

Totals

Overall Length	121.5 in
Maximum Torque	48.0 lb-ft @ 3500 rpm
Overall Width	64.0 in
Overall Height	77.2 in
Curb Weight	1768.4 lb**
Fuel Capacity	7.9 gal
Turning Radius	14.0 ft
Cargo Bed Capacity	1000 lb (600 lb for California models)
Load Capacity	1616 lb (1264 lb California model)
Seating Capacity	3
Towing Capacity	2000 lb

General

Final Drive	Selectable 2WD/4WD, shaft. Dual mode rear differential with differential lock
Cargo Bed Dimensions (LxWxH)	37.6 x 53.3 x 11.0 in
Lighting	(2) Halogen headlights, (2) LED headlights, (2) Halogen tail/brake lights
Instruments	Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators, seatbelt reminder lamps
Alternator Output (max)	75 amp
Color Choices	Metallic Phantom Silver, Candy Persimmon Red

Guarantee

Warranty	Kawasaki 3-Year Limited Warranty
----------	----------------------------------