



## Engine

Engine	2-stroke single with exhaust power valve, liquid-cooled
Transmission	6-speed, return shift, with wet multi-disc manual clutch
Displacement	84cc
Bore x Stroke	48.5 x 45.8mm
Compression Ratio	10.9:1 (low speed) - 9.0:1 (high speed)
Fuel System	28mm Keihin carburetor
Ignition	Electric CDI with digital advance

## Suspension

Rake/Trail	29°/3.8 in
Front Suspension / Wheel Travel	36mm inverted telescopic cartridge fork with 20-way compression damping/10.8 in
Rear Suspension / Wheel Travel	Uni-Trak® single shock system with 24-way compression and 21-way rebound damping, plus adjustable spring preload/10.8 in
Front Tire	70/100-17
Rear Tire	90/100-14
Ground Clearance	11.4 in
Wheelbase	49.8 in

## Brakes

Front Brakes	Single 220mm petal disc with dual-piston caliper
Rear Brakes	Single 220mm petal disc with single-piston caliper

## Totals

Overall Length	72.0 in
Overall Width	30.1 in
Overall Height	43.3 in
Seat Height	32.7 in
Curb Weight	165.3 lb**
Fuel Capacity	1.32 gal

## General

Frame Type	High-tensile steel perimeter design with subframe member
Final Drive	Chain
Color Choices	Lime Green

## Guarantee

Warranty	Not Available
----------	---------------