



## Engine

Engine	4-stroke, 55° V-twin, 4 valves per cylinder, SOHC, liquid-cooled
Transmission	5-speed with positive neutral finder
Displacement	903cc/55.10 cu in
Bore x Stroke	88.0 x 74.2mm
Compression Ratio	9.5:1
Fuel System	DFI® 34mm throttle bodies (2), with sub-throttle valves
Ignition	TCBI with digital advance

## Suspension

Rake / Trail	
Rake/Trail	33°/7.2 in
Front Suspension / Wheel Travel	41mm hydraulic telescopic fork/5.9 in
Rear Suspension / Wheel Travel	Uni-Trak® swingarm, 7-way adjustable spring preload/4.1 in
Front Tire	80/90x21
Rear Tire	180/70x15
Ground Clearance	5.5 in
Wheelbase	64.8 in

## Brakes

Front Brakes	Single 300mm hydraulic disc
Rear Brakes	Single 270mm hydraulic disc

## Totals

Overall Length	94.7 in
Maximum Torque	58.2 lb-ft @ 3500 rpm
Overall Width	35.2 in
Overall Height	44.1 in
Seat Height	27.0 in
Curb Weight	610.8 lb**
Fuel Capacity	5.3 gal

## General

Frame Type	Double cradle, high-tensile steel
Final Drive	Kevlar-reinforced belt
Color Choices	Metallic Matte Graphite Gray/Metallic Flat Spark Black

## Guarantee

Warranty	12 Month Limited Warranty
----------	---------------------------