



Engine

Engine	4-stroke, V-twin, SOHC, liquid-cooled
Starting System	Electric
Transmission	Automatic CVT (H,L,N,R)
Displacement	749cc
Bore x Stroke	85.0 x 66.0mm
Compression Ratio	9.3:1
Fuel System	DFI® with two 36mm throttle bodies
Ignition	Digital DC-CDI

Suspension

Front Suspension / Wheel Travel	Double wishbone/6.7 in
Rear Suspension / Wheel Travel	Double wishbone/7.5 in
Front Tire	AT 25 x 8-12
Rear Tire	AT 25 x 10-12
Ground Clearance	9.4 in
Wheelbase	50.6 in

Brakes

Front Brakes	Dual hydraulic 200mm discs with 2-piston calipers
Rear Brakes	Sealed, oil-bathed, multi-disc with independent park brake

Totals

Overall Length	86.4 in
Maximum Torque	42.7 lb-ft @ 4750 rpm
Overall Width	46.5 in
Overall Height	48.0 in
Seat Height	35.8 in
Curb Weight	699.0 lb**
Fuel Capacity	5.0 gal
Turning Radius	10.5 ft
Towing Capacity	1250 lb
Total Rack Capacity	242.0 lb
Rack Capacity, Front/Rear	88.0/176.0 lb

General

Frame Type	Double-cradle, high-tensile tubular steel
Track Front/Rear	36.4/35.0 in
Final Drive	Selectable 2WD/4WD with variable control front differential lock, shaft
Lighting	35W headlights, 5W taillight, 21W stoplight
Instruments	Speedometer, odometer, dual trip meters, fuel gauge, engine temp, clock, hour meter and 2WD/4WD icon, plus indicators for EPS, neutral, belt, and oil pressure

Color Choices Realtree Xtra® Green Camo

Guarantee

Warranty 12 Month Limited Warranty