



## Engine

|                   |   |
|-------------------|---|
| Park Brake Type   | Independent, Mechanical Disc                            |
| Engine            | 4-stroke, 3-cylinder, DOHC, liquid-cooled, gas          |
| Transmission      | Continuously Variable Transmission (CVT) with (H,L,N,R) |
| Displacement      | 812cc   |
| Bore x Stroke     | 2.83x2.62 in  |
| Compression Ratio | 9.5:1   |
| Fuel System       | DFI® with 34mm throttle body                            |
| Engine Braking    | Yes   |

## Suspension

|                                 |  |
|---------------------------------|--|
| Front Suspension / Wheel Travel | Double wishbone/8.7 in                       |
| Rear Suspension / Wheel Travel  | Double wishbone/8.5 (L) /8.7 (R) in          |
| Front Tire                      | 26x9.00-12, radial                           |
| Front Tires                     | 26x9.00-12, radial                           |
| Rear Tire                       | 26x11.00-12, radial                          |
| Rear Tires                      | 26x11.00-12, radial                          |
| Wheel Type                      | Steel  |
| Steering                        | Electric Power Steering (EPS), Tilt steering |
| Ground Clearance                | 10.2 in                                      |
| Wheelbase                       | 92.3 in                                      |

## Brakes

|              |                             |
|--------------|-----------------------------|
| Front Brakes | Dual Disc, 2 piston caliper |
| Rear Brakes  | Dual Disc, 1 piston caliper |

## Totals

|                    |   |
|--------------------|---|
| Overall Length     | 133.3 in  |
| Maximum Torque     | 48.0 lb-ft @ 3500 rpm   |
| Overall Width      | 64.0 in   |
| Overall Height     | 77.6 in   |
| Curb Weight        | 1916.1 lb**   |
| Fuel Capacity      | 7.9 gal   |
| Turning Radius     | 16.0 ft   |
| Cargo Bed Capacity | 1000 lb (3-person)<br>350 lb (6-person)<br>(600 lb for California models) |
| Load Capacity      | 1616 lb (1264 lb California model)  |
| Seating Capacity   | 3-person (1 row),<br>6 person (2 row)                                     |
| Towing Capacity    | 2000 lb   |

## General

|                              |  |
|------------------------------|--|
| Final Drive                  | Selectable 2WD/4WD, shaft. Dual mode rear differential with differential lock  |
| Cargo Bed Dimensions (LxWxH) | 42.7 x 53.7 x 11.0 in (3-person)<br>22.0 x 53.7 x 11.0 in (6-person)   |
| Lighting                     | (2) Halogen headlights, (2) Auxiliary LED headlights, (2) Halogen tail/brake lights  |
| Instruments                  | Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators, seatbelt reminder lamps |
| Alternator Output (max)      | 75 amp   |
| Color Choices                | Realtree Xtra® Green Camo  |

## Guarantee

|          |                                  |
|----------|----------------------------------|
| Warranty | Kawasaki 3-Year Limited Warranty |
|----------|----------------------------------|