



Engine

Engine	4-stroke, 2-cylinder, OHV 90° V Liquid-cooled
Transmission	Continuously Variable Transmission (CVT) with (H,L,N,R)
Displacement	617cc
Bore x Stroke	76.0 x 68.0mm
Compression Ratio	10.3:1
Fuel System	DFI® with 34mm Mikuni throttle body
Ignition	Digital electronic
Engine Braking	No

Suspension

Front Suspension / Wheel Travel	MacPherson Strut/3.9 in
Rear Suspension / Wheel Travel	DeDion Axle/2.8 in
Front Tires	23x11-10 tubeless
Rear Tires	23x11-10 tubeless
Steering	Rack-and-pinion
Ground Clearance	7.5 in
Wheelbase	73.6 in

Brakes

Front Brakes	4-wheel hydraulic drums, sealed
Rear Brakes	4-wheel hydraulic drums, sealed

Totals

Overall Length	116.7 in
Maximum Torque	34.7 lb-ft @ 2500 rpm
Overall Width	62.0 in
Overall Height	75.8 in
Curb Weight	1338.4 lb**
Fuel Capacity	6.3 gal
Turning Radius	11.0 ft
Cargo Bed Capacity	800 lb
Load Capacity	1327 lb
Seating Capacity	2
Towing Capacity	1200 lb

General

Frame Type	Steel tube ladder type
Final Drive	2WD, shaft. Dual mode rear differential with differential lock
Cargo Bed Dimensions (LxWxH)	46.3 x 51.6 x 11.4 in
Lighting	(2) Halogen headlights (2) tail/brake lights
Instruments	Parking brake warning light, coolant temperature warning light, horn, 12V DC outlet, fuel gauge, hour meter
Alternator Output (max)	23 amp
Color Choices	Timberline Green

Guarantee

Warranty	Kawasaki 3-Year Limited Warranty
----------	----------------------------------