



Engine

| | |
|----------------|---|
| Engine | 4-stroke, single-cylinder, SOHC, 4-valve, liquid-cooled |
| Transmission | Continuously Variable Transmission (CVT) with centrifugal clutch, (H,L,N,R) |
| Displacement | 695cc |
| Fuel System | DFI® with 44mm throttle body |
| Engine Braking | Yes |

Suspension

| | |
|---------------------------------|---|
| Front Suspension / Wheel Travel | Double wishbone/8.6 in |
| Rear Suspension / Wheel Travel | Double wishbone/9.1 in |
| Steering | Electric Power Steering (EPS) / rack-and-pinion |
| Ground Clearance | 10.6 in |
| Wheelbase | 78.9 in |

Totals

| | |
|--------------------|---|
| Overall Length | 110.0 in |
| Maximum Torque | 42.7 lb-ft @ 5000 rpm |
| Overall Width | 60.0 in |
| Overall Height | 74.4 in (EPS) / 75.8 (EPS LE, EPS Camo) |
| Curb Weight | 1587.6 lb (EPS) / 1594.2 (EPS LE) / 1598.6 (EPS Camo)** |
| Fuel Capacity | 9.5 gal |
| Turning Radius | 14.0 ft |
| Cargo Bed Capacity | 700 lb (600 lb California models) |
| Load Capacity | 1200 lb |
| Seating Capacity | 2 |
| Towing Capacity | 1500 lb |

General

| | |
|------------------------------|---|
| Final Drive | Selectable 2WD/4WD, shaft. Dual mode rear differential with differential lock |
| Cargo Bed Dimensions (LxWxH) | 33.4 x 44.1 x 9.1 in |
| Lighting | (2) Halogen (high/low beam) headlights and (2) LED headlights (high/low beam) |
| Instruments | Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, EPS warning indicators, neutral, reverse and parking indicators, differential indicator lamp, seatbelt reminder lamps |
| Alternator Output (max) | 35.7 amp |
| Color Choices | Firecracker Red |
| Guarantee | Kawasaki 3-Year Limited Warranty |
| Warranty | |