



Engine

Park Brake Type	Independent, Mechanical Drum
Engine	4-stroke, 2-cylinder, OHV 90° V Liquid-cooled, gas
Transmission	Continuously Variable Transmission (CVT) with (H,N,R)
Displacement	617cc
Bore x Stroke	2.99x2.68 in
Compression Ratio	10:3:1
Fuel System	DFI® with 34mm Mikuni throttle body
Engine Braking	No

Suspension

Front Suspension / Wheel Travel	MacPherson Strut/3.9 in
Rear Suspension / Wheel Travel	DeDion Axle/2.8 in
Front Tire	
Front Tires	23x11.00-10
Rear Tire	
Rear Tires	23x11.00-10
Wheel Type	Steel
Steering	Rack-and-pinion
Ground Clearance	7.5 in
Wheelbase	73.6 in

Brakes

Front Brakes	Drum
Rear Brakes	Drum

Totals

Overall Length	116.7 in
Maximum Torque	34.7 lb-ft @ 2500 rpm
Overall Width	62.0 in
Overall Height	75.8 in
Curb Weight	1338.4 lb**
Fuel Capacity	6.3 gal
Turning Radius	11.0 ft
Cargo Bed Capacity	800 lb
Load Capacity	1327 lb
Seating Capacity	2
Towing Capacity	1200 lb

General

Final Drive	2WD, shaft. Dual mode rear differential with differential lock
Cargo Bed Dimensions (LxWxH)	46.3 x 51.6 x 11.4 in
Lighting	(2) Halogen headlights, (2) tail/brake lights, (2) Halogen tail/brake lights
Instruments	Parking brake warning light, coolant temperature warning light, horn, 12V DC outlet, fuel gauge, hour meter
Alternator Output (max)	23 amp
Color Choices	Timberline Green, Dark Royal Red

Guarantee

Warranty	Kawasaki 3-Year Limited Warranty
----------	----------------------------------