



Engine

Park Brake Type	Independent, Mechanical Drum
Engine	4-stroke, single-cylinder, OHV, air-cooled, gas
Transmission	Continuously Variable Transmission (CVT) with (H,L,N,R)
Displacement	401cc
Bore x Stroke	3.23x2.99 in
Compression Ratio	8.6:1
Fuel System	Fuel injection
Engine Braking	No

Suspension

Front Suspension / Wheel Travel	MacPherson Strut/3.1 in
Rear Suspension / Wheel Travel	Unit Swingarm/3.1 in
Front Tire	
Front Tires	26x9.00-12
Rear Tire	
Rear Tires	26x9.00-12
Wheel Type	Alloy
Steering	Rack-and-pinion
Ground Clearance	8.1 in
Wheelbase	70.1 in

Brakes

Front Brakes	Drum
Rear Brakes	Drum

Totals

Overall Length	106.7 in
Maximum Torque	21.4 lb-ft @ 2400 rpm
Overall Width	52.6 in
Overall Height	75.0 in
Curb Weight	1098.1 lb**
Fuel Capacity	4.2 gal
Turning Radius	11.8 ft
Cargo Bed Capacity	400 lb
Load Capacity	884 lb
Seating Capacity	2
Towing Capacity	1100 lb*

General

Final Drive	Selectable 2WD/4WD, shaft. Dual mode rear differential with differential lock
Cargo Bed Dimensions (LxWxH)	35.6 x 40.9 x 9.6 in
Lighting	(4) LED headlights, (2) Halogen tail/brake lights
Instruments	Fuel gauge, hour meter, oil temp light, parking brake light
Alternator Output (max)	22.9 amp
Color Choices	Super Black

Guarantee

Warranty	Kawasaki 3-Year Limited Warranty
----------	----------------------------------