



Engine

Engine	4-stroke, 1-cylinder, OHV, air-cooled
Transmission	2-speed, automatic, reverse, High, Low, Neutral, Reverse
Displacement	401cc
Bore x Stroke	82.0 x 76.0mm
Compression Ratio	8.6:1

Suspension

Rear Suspension / Wheel Travel	Unit swing axle/3.1 in
Front Suspension / Wheel Travel	MacPherson strut/3.1 in
Front Tires	26x9-12 Duro Bias, alloy wheels
Rear Tires	26x9-12 Duro Bias, alloy wheels
Steering	Rack-and-pinion
Ground Clearance	8.1 in
Wheelbase	70.1 in

Brakes

Front Brakes	Hydraulic drum
Rear Brakes	Hydraulic drum

Totals

Overall Length	106.7 in
Maximum Torque	21.7 lb-ft @ 2400 rpm
Overall Width	52.6 in
Overall Height	75.0 in
Curb Weight	1098.1 lb**
Fuel Capacity	4.2 gal
Turning Radius	11.8 ft (differential unlocked)
Cargo Bed Capacity	400 lb
Load Capacity	884 lb
Seating Capacity	2
Towing Capacity	1100 lb

General

Final Drive	Shaft-driven selectable 4-wheel drive, dual-mode rear differential, 2WD/4WD/rear differential lock
Cargo Bed Dimensions (LxWxH)	35.6 x 40.9 x 9.6 in
Lighting	(4) LED headlights (2) Halogen headlights Tail/brake lights
Instruments	Fuel gauge, hour meter, oil temp light, parking brake light
Alternator Output (max)	17 amp

Guarantee

Warranty	Kawasaki 3-Year Limited Warranty
----------	----------------------------------