



## Engine

Engine	4-stroke, 3-cylinder, DOHC, liquid-cooled, gas
Transmission	Continuously Variable Transmission (CVT) with (H,L,N,R)
Displacement	812cc
Fuel System	DFI® with 34mm throttle body
Engine Braking	Yes

## Suspension

Front Suspension / Wheel Travel	Double wishbone/8.7 in
Rear Suspension / Wheel Travel	Double wishbone/8.5/8.7 in
Steering	Electric Power Steering (EPS) / rack-and-pinion
Ground Clearance	10.8 in
Wheelbase	79.7 in

## Totals

Overall Length	121.5 in
Maximum Torque	48.0 lb-ft @ 3500 rpm
Overall Width	64.0 in
Overall Height	77.2 in
Curb Weight	1768.4 lb**
Fuel Capacity	7.9 gal
Turning Radius	14.0 ft
Cargo Bed Capacity	1000 lb (600 lb for California models)
Load Capacity	1616 lb
Seating Capacity	3
Towing Capacity	2000 lb

## General

Final Drive	Selectable 2WD/4WD, shaft. Dual mode rear differential with differential lock
Cargo Bed Dimensions (LxWxH)	37.6 x 53.3 x 11.0 in
Lighting	(2) Halogen (high/low beam) headlights. (2) additional auxiliary LED headlights (high/low beam)

## Instruments

Instruments	Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators, seatbelt reminder lamps
-------------	--

## Alternator Output (max)

Alternator Output (max)	75 amp
Color Choices	Atomic Silver, Candy Plasma Blue

## Guarantee

Warranty	Kawasaki 3-Year Limited Warranty
----------	----------------------------------