



Engine

Engine	4-stroke, V-twin, SOHC, liquid-cooled
Starting System	Electric
Transmission	2-Speed automatic, reverse
Displacement	749cc
Bore x Stroke	85.0 x 66.0mm
Compression Ratio	9.3:1
Fuel System	DFI® with two 36mm throttle bodies
Ignition	Digital DC-CDI

Suspension

Front Suspension / Wheel Travel	Double wishbone/6.7 in
Rear Suspension / Wheel Travel	Full independent, dual A-arm/7.5 in
Front Tire	AT 25 x 8-12
Rear Tire	AT 25 x 10-12
Ground Clearance	9.4 in
Wheelbase	50.6 in

Brakes

Front Brakes	Dual hydraulic 176mm discs with 2-piston calipers
Rear Brakes	Sealed, oil-bathed, multi-disc

Totals

Overall Length	86.4 in
Maximum Torque	42.7 lb-ft @ 4750 rpm
Overall Width	46.5 in
Overall Height	48.0 in
Seat Height	35.8 in
Curb Weight	699.0 lb**
Fuel Capacity	5.0 gal
Turning Radius	10.5 ft
Towing Capacity	1250 lb
Total Rack Capacity	242.0 lb
Rack Capacity, Front/Rear	88.0 lb/176.0 lb

General

Frame Type	Double-cradle, high-tensile tubular steel
Track Front/Rear	36.4/35.0 in
Final Drive	Selectable 4WD with variable front differential control, shaft
Lighting	35W headlights, 5W taillight, 21W stoplight
Instruments	Speedometer, odometer, dual trip meters, fuel gauge, engine temp, clock, hour meter and 2WD/4WD icon, plus indicators for EPS, neutral, belt, and oil pressure
Color Choices	Metallic Stardust White, Vibrant Blue, Super Black

Guarantee

Warranty	12 Month Limited Warranty
----------	---------------------------